

# DV51 Tower/Spreader



The Deck Vision DV51 Tower / Spreader light is designed to provide high powered LED flood lighting utilizing a flush mounted weld in flange. Suitable for sport fishing towers, arches, mast spreaders, etc. the DV51 incorporates the latest advances in driver technology including heat management to ensure optimum performance and longevity. A weld in flange is provided to mount the fitting which has (patent pending) advanced LED optics creating a wide flood effect suitable for even the larger cockpits and deck areas.

## DV51 technical specs

Application for:	Towers and Spreader
Glass Lens:	Convex cylindrical
Power Supply:	11-28 volt d.c. - 1.47 amps
Light Source:	White or blue LED array
Life Length:	Approx. 10,000 hours
Dimensions:	Length: 7.48" (190mm) Height: 1.73" (44mm) Thickness: 1.14" (29mm) Without weld in adapter
Construction:	Black nylon and bright dip anodized marine aluminum alloy
IP rating:	68

*Note: All information is subject to change without prior notice, please confirm details prior to ordering.*



Patent Pending



277 SW 33rd Court, Fort Lauderdale, FL 33315 USA  
T. 954 760 4447 Toll Free 1 866 772 0130 F. 954 525 3261  
sales@seavision.com www.seavision.com